Transponder Chip User Manual

I. Warning & Safety Information

⚠.Do not disassemble arbitrarily to prevent damage.

II. Product Name

1. Transponder Chip

III. Model: XT27A

IV. Instructions for Use

Step 1: Put the WDI super chip into the keytool and open the xhorse app.

Step 2: Go to keytool and select special functions

Step 3: Select "Set type of WDI super transponder

Step 4: Scroll down to Reset WDI super chip. It' s the last option on that page Step

5: Tap set



V. Precautions

The Xhorse WDI super chips have to be reset to reuse them.

VI. Features

Can be used as the chips below for auto key programming:

Chip 7935 33 4041 4243 44

Chip 7930 46

Chip 7930 47

Chip 7930 4D chip on board

Chip 7930 45 chip on board

Chip 7937 46 chip on board

Chip 7947 47 chip on board

Chip 4D 60 6370 8083 82G 67

Chip 4E 64

Chip 4C

Chip 8C

Chip 8A Toy-ota H chip/Hyundai

Chip 43 VAG/Ho-nda

Chip 8E Au-di/Ho-nda

Chip T3 Bu-ick model

Chip T1/T2/T3

VII. Support For Wvdi2,wvdi key tool,mini key tool,key toolmax,key tool plus